



## Technical features



RAL 9016 standard 
 Stainless steel 
 Other colors on request 



Range  
Up to 4,2 m



Airflow / Length  
1800 - 7200 m<sup>3</sup>/h  
1 m to 3 m



Fans  
Centrifugal  
5-speed



Heating types  
A: unheated



Heating capacity  
-



Control  
Plug&Play manual regulator  
+ IR remote control  
(Optional Clever Control)



Casing  
Galvanised steel /  
Stainless Steel



Grille type  
Circular perforated



Outlet lamellas  
Aluminium, airfoil type  
Adjustable 0-15° each side

KOOL unheated air curtain ensures a low turbulence high velocity air jet, thus efficiently separating spaces with high temperature differences. With a compact timeless design provided with a faceted inlet grille avoiding intensive maintenance. It works with double-inlet centrifugal fans driven by an external rotor motor and low noise level. EC models assembled with very low consumption efficiency fans.

Includes Plug&Play control with 7m RJ45 cable and infrared remote control. Optionally can be regulated with Advanced Clever Control (programmable, automatic, intelligent, compatible with Modbus RTU for BMS).

### ❄️ UNHEATED


Model	Airflow m <sup>3</sup> /h	Ventilation power 230V~50Hz kW	Ventilation current 230V~50Hz A	Noise Level (5 m) dB(A)	Weight kg
KM 1000 A	1800	0,212	0,94	55	29
KM 1500 A	2700	0,318	1,41	56	44
KM 2000 A	3600	0,424	1,88	57	53
KM 2500 A	4500	0,530	2,35	58	58
KM 3000 A	5400	0,636	2,82	59	76
KECM 1000 A	1840	0,142	1,24	56	33
KECM 1500 A	2760	0,213	1,86	57	50
KECM 2000 A	3680	0,284	2,48	58	61
KECM 2500 A	4600	0,355	3,10	59	68
KECM 3000 A	5520	0,426	3,72	60	76
KG 1000 A	2400	0,642	2,85	57	37
KG 1500 A	3200	0,856	3,80	58	55
KG 2000 A	4800	1,284	5,70	59	71
KG 2500 A	5600	1,498	6,65	60	78
KG 3000 A	6400	1,712	7,60	61	86
KECG 1000 A	2700	0,213	1,86	61	37
KECG 1500 A	3600	0,284	2,48	62	56
KECG 2000 A	5400	0,426	3,72	63	71
KECG 2500 A	6300	0,497	4,34	64	78
KECG 3000 A	7200	0,568	5,96	65	86



Selection program



## Dimensions



## Optional accessories

### Supports




Wall rail support  
SPWR



Silentblock supports  
SPANG-SIL / SLB




Suspension cables  
SPCT



Omega wall support  
SPT3



Foot support  
SPF-KOOL  
(Galv. / SS)



Joining kit  
SPJ-KOOL  
(Galv. / SS)

### Control



IR Control  
✓ Included



Basic Control CA-5AW-IR  
✓ Included



Hand-Auto  
CH-5HW-NE



Clever Control Kit



Interface kit  
IN-NE-II



RJ45 Cable  
✓ Included

### Sensors



Mechanical door contact  
MEC-DC



Magnetic door contact  
MAG-DC



External Temperature  
Sensor (Clever Control)

CAD drawings, BIM files, installation  
manuals and other documentation

