



Characteristics



- Directional rotation selector
- Releasing button
- Universal flange for shifts Ø8 a Ø21 mm and square from 6 to 12 mm
- Models of 16 Nm for shutters till 3 m², 25 Nm models for shutters till 4,5 m² and 40 Nm models for doors till 7,5 m² depending on manufacturer

Specifications

Model	Torque (Nm)	Tension (V (50 Hz))	Control	Running Time 90° (s)	Auxiliar Contact	Feedback signal (kOhm)
TG 230	25	230AC	T/N, 3P	60 -150	-	-
TG 230 P1	25	230AC	T/N, 3P	60 -150	-	10
TG 230 S2	25	230AC	T/N, 3P	60 -150	2x3A	-
TG 24	25	24AC	T/N, 3P	60 -150	-	-
TG 24 P1	25	24AC	T/N, 3P	60 -150	-	10
TG 24 R	25	24AC	0,,,10V	60 -150	-	-
TG 24 S2	25	24AC	T/N, 3P	60 -150	2x3A	-
TL 230	40	230AC	T/N, 3P	60 -180	-	-
TL 230 P1	40	230AC	T/N, 3P	60 -180	-	10
TL 230 S2	40	230AC	T/N, 3P	60 -180	2x3A	-
TL 24	40	24AC	T/N, 3P	60 -180	-	-
TL 24 P1	40	24AC	T/N, 3P	60 -180	-	10
TL 24 R	40	24AC	0,,,10V	60 -180	-	-
TL 24 S2	40	24AC	T/N, 3P	60 -180	2x3A	-
TM 230	16	230AC	T/N, 3P	50 -100	-	-
TM 230 P1	16	230AC	T/N, 3P	50 -100	-	10
TM 230 S2	16	230AC	T/N, 3P	50 -100	2x3A	-
TM 24	16	24AC	T/N, 3P	50 -100	-	-
TM 24 P1	16	24AC	T/N, 3P	50 -100	-	10
TM 24 R	16	24AC	0,,,10V	50 -100	-	-
TM 24 S2	16	24AC	T/N, 3P	50 -100	2x3A	-