



## Characteristics



- External rotor motor protected through thermal contact
- Variable speed 0-100%
- Impellers balanced statically and dynamically according ISO 1940
- Low noise level
- Three phase version on request

## Specifications

| Model          | Tension<br>(V (50 Hz)) | Current fans<br>(A) | Power<br>(W) | Speed<br>(rpm) | Air Flow<br>(m <sup>3</sup> /h) | Maximum Pressure<br>(Pa) |
|----------------|------------------------|---------------------|--------------|----------------|---------------------------------|--------------------------|
| 2GRE15 133/49R | 1x230V                 | 0,33                | 75           | 2210           | 255                             | 330                      |
| 2GRE15 140/59R | 1x230V                 | 0,39                | 88           | 1245           | 340                             | 400                      |
| 2GRE20 140/59R | 1x230V                 | 0,56                | 125          | 1540           | 395                             | 440                      |
| 2GRE25 140/59R | 1x230V                 | 0,78                | 176          | 2050           | 515                             | 450                      |
| 2GRE35 160/62R | 1x230V                 | 0,72                | 165          | 1565           | 465                             | 530                      |
| 2GRE45 160/62R | 1x230V                 | 1,12                | 253          | 2110           | 625                             | 610                      |
| 2GRE45 120/62R | 1x230V                 | 0,27                | 58           | 1715           | 260                             | 280                      |
| 2GRF65 180/52R | 1x230V                 | 1,79                | 411          | 2145           | 685                             | 900                      |
| 4GRE25 160/62R | 1x230V                 | 0,34                | 70           | 1280           | 410                             | 160                      |
| 4GRE25 180/75R | 1x230V                 | 0,4                 | 89           | 985            | 530                             | 220                      |
| 4GRE35 180/75R | 1x230V                 | 0,45                | 102          | 1155           | 585                             | 220                      |
| 4GRE45 200/75R | 1x230V                 | 0,87                | 172          | 1040           | 775                             | 280                      |