



## Characteristics



- Casing made of welded or folded steel sheet
- Welded sheet steel impeller with backward curved blades balanced statically and dynamically
- Very quiet operation virtue
- Special executions for high temperatures
- 16 possible orientations

## Specifications

| Model   | Tension<br>(V (50 Hz)) | Current fans<br>(A) | Power fans<br>(kW) | Speed<br>(rpm) | Air Flow<br>(m <sup>3</sup> /h) | Maximum Pressure<br>(Pa) |
|---------|------------------------|---------------------|--------------------|----------------|---------------------------------|--------------------------|
| MAR 310 | 3x400V                 | 1,42                | 0,55               | 2800           | 1400                            | 1580                     |
| MAR 350 | 3x400V                 | 2,69                | 1,1                | 2800           | 2000                            | 2200                     |
| MAR 400 | 3x400V                 | 3,73                | 1,5                | 2800           | 2800                            | 2750                     |
| MAR 450 | 3x400V                 | 7,65                | 3                  | 2800           | 4000                            | 3400                     |
| MAR 501 | 3x400V                 | 9,21                | 4                  | 2800           | 2750                            | 4500                     |
| MAR 502 | 3x400V                 | 12,2                | 5,5                | 2800           | 6000                            | 4500                     |
| MAR 571 | 3x400V                 | 16,5                | 7,5                | 2800           | 4500                            | 6000                     |
| MAR 572 | 3x400V                 | 23,5                | 11                 | 2800           | 9000                            | 6000                     |
| MAR 631 | 3x400V                 | 23,5                | 11                 | 2800           | 5000                            | 7250                     |
| MAR 632 | 3x400V                 | 30,59               | 15                 | 2800           | 9000                            | 7250                     |
| MAR 711 | 3x400V                 | 46,25               | 18,5               | 2800           | 5000                            | 9400                     |
| MAR 712 | 3x400V                 | 55                  | 22                 | 2800           | 8000                            | 9400                     |
| MAR 713 | 3x400V                 | 75                  | 30                 | 2800           | 18000                           | 9400                     |