



Characteristics



- Directly connected motor
- Casing made of steel welded or clamped
- Forward curved impellers, balanced statically and dynamically
- Maximum temperature of the air 90°C
- Special versions for high temperatures optional
- EX anti-explosion execution optional

Specifications

| Model | Tension (V (50 Hz)) | Current fans (A) | Power fans (kW) | Speed (rpm) | Air Flow (m³/h) | Maximum Pressure (Pa) |
|--------|------------------------|---------------------|--------------------|----------------|--------------------|--------------------------|
| MM 201 | 3x400V | 2 | 0,75 | 2800 | 2000 | 1200 |
| MM 202 | 3x400V | 2,6 | 1,1 | 2850 | 2250 | 1200 |
| MM 251 | 3x400V | 3,9 | 1,5 | 2850 | 3000 | 1800 |
| MM 252 | 3x400V | 5 | 2,2 | 2850 | 4200 | 1800 |
| MM 301 | 3x400V | 11,5 | 5,5 | 2850 | 5000 | 2500 |
| MM 302 | 3x400V | 15,6 | 7,5 | 2850 | 7000 | 3500 |
| MM 351 | 3x400V | 15,6 | 7,5 | 2850 | 7000 | 3500 |
| MM 352 | 3x400V | 23,5 | 11 | 2850 | 10000 | 3500 |
| MM 353 | 3x400V | 31,2 | 15 | 2850 | 12000 | 3500 |