

## Characteristics



- Plastic polyester frame. Rigid
- Microfiber-glass filtering blanket, pleated with the "mini-pleat system"
- It is non corrosive, completely incinerable and respectful with the environment

## Specifications

| Model        | Dimensions<br>(mm) | Efficiency EN 779 / EN 1882 | Air Flow<br>(m <sup>3</sup> /h) | Initial Pressure<br>(Inc. Pa) |
|--------------|--------------------|-----------------------------|---------------------------------|-------------------------------|
| D10 12X24X12 | 287x592x292        | H10                         | 1450                            | 170                           |
| D10 20X24X12 | 490x592x292        | H10                         | 2450                            | 170                           |
| D10 24X24X12 | 592x592x292        | H10                         | 3000                            | 170                           |
| D13 12X24X12 | 287x592x292        | H13                         | 1450                            | 250                           |
| D13 20X24X12 | 490x592x292        | H13                         | 2450                            | 250                           |
| D13 24X24X12 | 592x592x292        | H13                         | 3000                            | 250                           |
| D7 12X24X12  | 289x592x292        | F7                          | 2100                            | 125                           |
| D7 20X24X12  | 490x592x292        | F7                          | 3400                            | 125                           |
| D7 24X24X12  | 592x592x292        | F7                          | 4250                            | 125                           |
| D9 12X24X12  | 287x592x292        | F9                          | 2100                            | 160                           |
| D9 20X24X12  | 490x592x292        | F9                          | 3400                            | 160                           |
| D9 24X24X12  | 592x592x292        | F9                          | 4250                            | 160                           |