



Characteristics

Kitchen extractor fan with internal fibreglass insulation that reduces noise. It has a high-performance turbine with self-cleaning effect and, thanks to the hinged service door, manual cleaning is also facilitated. You can choose whether the discharge is from the top or the side depending on the installation.



- Casing made from aluminium profile and galvanized steel sandwich type with internal fibreglass insulation
- Backward curved impeller of high performance with self-cleaning effect
- Folding gate to lighten the cleansing of the impeller
- Motors standard IEC controllable through frequency changes
- Upper or lateral discharge to choose

Specifications

Model	Tension (V (50 Hz))	Current fans (A)	Power fans (kW)	Speed (rpm)	Air Flow (m ³ /h)	Maximum Pressure (Pa)
KAFD 250-2	3x400V	1,67	0,55	2730	2200	750
KAFD 280-2	3x400V	1,96	0,75	2740	3200	950
KAFD 315-2	3x400V	2,6	1,1	2670	4300	1400
KAFD 315-4	3x400V	1,4	0,37	1360	2200	300
KAFD 355-4	3x400V	1,4	0,55	1360	3400	380
KAFD 400-4	3x400V	2,5	0,75	1350	4800	500
KAFD 450-4	3x400V	3,3	1,1	1350	6500	650
KAFD 500-4	3x400V	4,3	1,5	1330	9000	800
KAFE 250-2	1x230V	3,8	0,55	2820	2200	750
KAFE 280-2	1x230V	5,1	0,75	2800	3200	950
KAFE 315-2	1x230V	6,3	1,1	2820	4300	1400
KAFE 315-4	1x230V	3,3	0,37	1350	2200	300
KAFE 355-4	1x230V	3,3	0,37	1350	3400	380
KAFE 400-4	1x230V	5,1	0,75	1370	4800	500
KAFE 450-4	1x230V	7,6	1,1	1360	6500	650