



Characteristics



- EC Motor of low consume protected through thermal contact with electrical regulation integrated
- Variable speed with signal 0-10V or 4-20 mA
- Backward curved impellers balanced statically and dinamically according to ISO 1940, class G 2,5
- Low height for false ceiling installation
- Some models available with acoustic insulation. Consult
- WS = Sound Absorbing Casing

Specifications

| Model | Tension (V (50 Hz)) | Current fans (A) | Power fans (kW) | Speed (rpm) | Air Flow (m³/h) | Maximum Pressure (Pa) | ERP Normative |
|-------------------|---------------------|------------------|-----------------|-------------|-----------------|-----------------------|---------------|
| KHAG 225.3BK W | 1x230V | 1,1 | 0,16 | 3200 | 1070 | 725 | ERP 2018 |
| KHAG 250.3DE W | 1x230V | 1 | 0,24 | 2770 | 1455 | 690 | ERP 2018 |
| KHAG 280.4EA W | 1x230V | 2,8 | 0,45 | 2400 | 2480 | 690 | ERP 2018 |
| KHAG 280.4EA WS | 1x230V | 2,8 | 0,45 | 2400 | 2460 | 690 | ERP 2018 |
| KHAG 315.4EA W | 1x230V | 1,3 | 0,21 | 1650 | 420 | 2050 | ERP 2018 |
| KHAG 315.4EA WS | 1x230V | 1,3 | 0,21 | 1650 | 420 | 2050 | ERP 2018 |
| KHAG 315.5FA W | 1x230V | 3,73 | 0,84 | 2600 | 3160 | 1000 | ERP 2018 |
| KHAG 315.5FA WS | 1x230V | 3,73 | 0,84 | 2600 | 3160 | 1000 | ERP 2018 |
| KHAG 355.4EA W | 1x230V | 2,2 | 0,37 | 1500 | 3500 | 430 | ERP 2018 |
| KHAG 355.4EA WS | 1x230V | 2,2 | 0,37 | 1500 | 3500 | 430 | ERP 2018 |
| KHAG 355.5FA W | 3x400V | 1,06 | 0,6 | 1800 | 3800 | 620 | ERP 2018 |
| KHAG 355.5FA W-3 | 3x400V | 1,2 | 0,6 | 1800 | 3800 | 620 | ERP 2018 |
| KHAG 355.5FA WS | 1x230V | 2,7 | 0,6 | 1800 | 3850 | 625 | ERP 2018 |
| KHAG 355.5FA WS-3 | 3x400V | 1,2 | 0,6 | 1800 | 3800 | 620 | ERP 2018 |
| KHAG 400.5FA W | 3x400V | 1,7 | 0,96 | 1700 | 4750 | 680 | ERP 2018 |
| KHAG 400.5FA W-3 | 3x400V | 1,5 | 0,8 | 1700 | 4750 | 720 | ERP 2018 |
| KHAG 400.5FA WS | 1x230V | 3,55 | 0,8 | 1700 | 4800 | 690 | ERP 2018 |
| KHAG 400.5FA WS-3 | 3x400V | 1,5 | 0,8 | 1700 | 4750 | 720 | ERP 2018 |
| KHAG 450.5FA W | 1x230V | 3,72 | 0,84 | 1450 | 5570 | 600 | ERP 2018 |
| KHAG 450.5FA WS | 1x230V | 3,72 | 0,84 | 1450 | 5570 | 600 | ERP 2018 |
| KHAG 450.5HF W | 3x400V | 2,4 | 2,3 | 1700 | 6500 | 850 | ERP 2018 |
| KHAG 450.5HF WS | 3x400V | 2,3 | 1,3 | 1700 | 6500 | 850 | ERP 2018 |
| KHAG 500.6FF W | 3x400V | 3,1 | 2 | 1500 | 9800 | 900 | ERP 2018 |
| KHAG 500.6FF WS | 3x400V | 3 | 1,9 | 1500 | 9800 | 900 | ERP 2018 |
| KHAG 560.6IF W | 3x400V | 3,8 | 2,4 | 1400 | 11750 | 880 | ERP 2018 |
| KHAG 560.6IF WS | 3x400V | 4,1 | 2,6 | 1400 | 11750 | 880 | ERP 2018 |