




Characteristics



- Casing made of extruded aluminium of triple chamber
- Casing made from galvanized steel sandwich type with internal fiberglass insulation 20 mm thick
- Belt driven motors normalized IEC to be calculated depending on the working point Low noise level Special Special executions and higher capacity on request
- Versions:
 - TRZ Models with forward curved impellers
 - HRZ Models with backward curved impellers

Specifications

| Model | Air Flow Up To (m³/h) | Motor Power Available (kW) |
|--------------------|-----------------------|----------------------------|
| AIRBOX 100 HRZ 355 | 16700 | - |
| AIRBOX 100 HRZ 400 | 23800 | - |
| AIRBOX 100 TRZ 355 | 19000 | - |
| AIRBOX 100 TRZ 400 | 20500 | - |
| AIRBOX 127 HRZ 200 | 32700 | - |
| AIRBOX 127 HRZ 450 | 28500 | - |
| AIRBOX 127 TRZ 450 | 25500 | - |
| AIRBOX 127 TRZ 500 | 29000 | - |
| AIRBOX 150 HRZ 560 | 40700 | - |
| AIRBOX 150 HRZ 630 | 47500 | - |
| AIRBOX 150 TRZ 560 | 37000 | - |
| AIRBOX 150 TRZ 630 | 43000 | - |
| AIRBOX 50 HRZ 180 | 4800 | - |
| AIRBOX 50 HRZ 200 | 5300 | - |
| AIRBOX 50 TRZ 180 | 5500 | - |
| AIRBOX 50 TRZ 200 | 6100 | - |
| AIRBOX 67 HRZ 225 | 6900 | - |
| AIRBOX 67 HRZ 250 | 9800 | - |
| AIRBOX 67 TRZ 225 | 7800 | - |
| AIRBOX 67 TRZ 250 | 9200 | - |
| AIRBOX 80 HRZ 280 | 11300 | - |
| AIRBOX 80 HRZ 315 | 13000 | - |
| AIRBOX 80 TRZ 280 | 12000 | - |
| AIRBOX 80 TRZ 315 | 15500 | - |